



PRODUCT SPECIFICATION

SPECIFICATION

Product Name

EOLO SUPER 4T 15 W-40 / EOLO SUPER 4T 15W-40

PRIMARY TESTS	METHOD	SPECIFICATION		
		MIN	TYP	MAX
Appearance	Visual		Clear and Bright	
Colour	ASTM D1500 / TS 1713 ISO 2049	2	3	4
Density 15°C, g/ml	ASTM D4052 / TS EN ISO 12185	0.870	0.880	0.900
Viscosity 100 °C, mm ² /s	ASTM D445 / TS 1451 EN ISO 3104	13	14	16
Viscosity 40 °C, mm ² /s	ASTM D445 / TS 1451 EN ISO 3104	90	110	130
Viscosity Index	ASTM D2270 / TS ISO 2909	135	137	

SECONDARY TESTS	METHOD	SPECIFICATION		
Pour Point, °C	ASTM D97 / TS 1233 ISO 3016			-18
Flash Point, °C (COC)	ASTM D92 / TS EN ISO 2592	220		
T.B.N. mgKOH/g	ASTM D2896 / TS 5655 ISO 3771	5		
Sulfated Ash %m/m	ASTM D874 / TS ISO 3987			1,2
Foaming Characteristic (I,II,III Kd.) ml/l	ASTM D892 / TS 1834 ISO 6247	10/0	50/0	10/0
Phosphorus Content. %	ASTM D4951	0,08		0,12

PERFORMANCE LEVELS : API : SJ / CF, JASO MA, JASO MA2

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical datas about the products and product packagings, please contact with M Oil.